


APPLICATION INSTRUCTION

Bird deterrent strips semaSORB PROBIRD - TAPE



se ma Gesellschaft für Innovationen mbH
Industriestraße 12
D-06869 Coswig / GERMANY
Phone: +49(0)34903 30467
Telefax: +49(0)34903 30465
E-Mail: info@sema-gmbh.com
www.sema-gmbh.com




- 1.**
Cut the strips to size.
Add a bleed of 5mm.

Application equipment:

- Scissors & ruler
- Spray bottle with assembly solution
(water with several drops of assembly concentrate)
- Clean, soft cloth or kitchen roll
- Cutter
- Squeegee with felt




- 2.**
Clean and dry the
glass and the frame.



- 6.**
Completely remove
the water moving the
squeegee vertically
down and up.




- 3.**
Use 2 adhesive strips to
remove the protective
film from the adhesive.



Abstand = 1 Streifenbreite


- 7.**
Repeat steps 4+5 – spray the
entire adhesive side of the strip
with assembly solution –
Position the strips flush with the
top maintaining a distance of
one strip width to the last film
strip.



- 4.**
Spray the entire
adhesive side of the
strip with assembly
solution.



- 8.**
Repeat step 6 – Completely
remove the water moving the
squeegee vertically down
and up – Continue until the
glass surface to be equipped
is covered with strips.



Abstand = 1 Streifenbreite

- 5.**
Position the strip flush
with the top maintaining
a distance of one strip
width to the window
frame – you can use 1
film strip as application
aid.



- 9.**
If necessary, cut the film
strips to fit within the frame.
Use a squeegee to dry the
edge. Use a soft cloth/
kitchen roll to carefully
absorb the residual moisture
on the frame.

WARNING! NEVER clean the films dry!



Instruction

for attaching bird protection tape to windows
semaSORB **PROBIRD400® Tape**/ semaSORB **PROBIRD500® Tape**

Video- Link: https://www.youtube.com/watch?v=0oLidun_Kj8

1. Cut strips

Length of strips + 5 mm bleed1.

2. Cleaning the glass surface

The glass surface is sprayed with a mixture of water, a detergent and a little spirit and cleaned. Remove the glass surface with a rubber wiper.

3. Applying the template

The 1st strip (protective foil still left) can be applied to the edge of the glass as an application template and then the adhesive tapes can be attached at the top and bottom in such a way that they can be easily removed.

4. Spray the window wet

Spray the window wet with the assembly spray solution (0.5 l water + a few splashes of assembly concentrate).

5. Remove the protective film from the bird protection tapes

Remove the protective film from the bird protection strip using 2 adhesive strips and apply to the wet surface. Apply glass surface upside down. - The adhesive side points to you. -

6. Mounting on glass

Now spray the adhesive side and turn the strip over, place it on the glass and add the water with the squeegee. Completely spread out the supplied plastic squeegee. Starting from the top, then vertically downwards. For lay cross stripes from one side to the other. If necessary, carry out this procedure repeat.

Again and again spray the outside of the foil wet and only then paint it out !

Note:

The glass surface should always be sprayed very well. The assembly spray solution can be used to spray the glass surface. Push the bird protection tapes back and forth for a while until they are in the desired position. When applying to plastic surfaces, it is imperative that you test them in one place beforehand!

7. Repetition of steps 5 and 6

Place the previously removed silicone strip flush with the first bird protection tape. This will even distance between the bird protection tapes. Now the next bird protection tape. Then remove the silicone strip again and place it on the second tape flush. Repeat the process until the glass surface is covered or all tapes are used up.

8. Cut bird protection tapes to size

Cut the bird protection tapes at the end of the frame carefully with a cutting knife and place them on the frame. Make sure that the tapes do not slip. The remaining moisture along the frame with a soft cloth / carefully absorb the paper towel. Some of the freshly laid strips are still cloudy. This turbidity disappears within approx. 30 days after assembly. This process may take longer in cold seasons.

9. Notes

semaSORB-PROBIRD Tapes can be cleaned 30 days after installation with a window cleaner. (except TFT, LCD monitor detergents) that do not contain scouring agents. Hard do not use sponges, microfibre cloths, coarse cloths or brushes. Recommended soft sponges, soft cloths, soft felt wipers and rubber wipers..

Never clean foils dry.

The optimum temperature of the surface to be covered is between 15 degrees Celsius and 25 degrees Celsius. Solar radiation heats up the glass surface too much and should therefore be avoided during installation will be! If the pane is too hot, bubbles will form under the film, which will not be removed afterwards. Micro particles causes the slightest curvature visible to the naked eye.

Therefore, make sure that the glass surface is thoroughly cleaned. Adhesive residues on the surface of the glass can be removed well with spirit. Please ensure good ventilation.